



## A Proven Instrument for Absolute Liquid Level Measurement

### Aquatrak<sup>®</sup> 5000 Series Sensor



Sensor with Waterproof Connectors



Sensor with Watertight Connectors

#### Applications

- Tide and Sea State
- River Stage
- Groundwater
- Head/Tail Water
- Tank Ullage

#### Technology

Unique patented means of ratio metric time comparisons of sequential sonic/pressure pulses. Environmentally protected within a small diameter ranging tube. Aquatrak instruments reliably provide performance unequalled in the industry.

#### Accuracy

Self-calibrated measurement correction for ambient temperature, pressure, and gas density within the calibrated range(s); yields accuracy of better than  $\pm 3\text{mm}$ .

#### Reliability

Non-mechanical implementation with no bushings, bearings, gears, floats, or immersed active elements. Aquatrak sensors have a field-proven reliability record of better than 1,000,000 hours MTBF

#### Versatility

The all-digital 5000 Sensor with internal microcomputer relieves the host system of level measurement routines. RS-232 and SDI-12 interfaces make it compatible with commonly-used data loggers, computers, controllers, and modems.

#### Product Enhancements

The Aquatrak 5000 Series continues the tradition of accuracy and reliability of its predecessors. Added capabilities and features include:

- Repackaged as a single integrated unit. The electronics is now in the sensor head.
- Reduced power consumption.
- Includes three external temperature probes.
- Concurrent Measurements.

#### Battery Powered

The sensor is designed for continuous long-term unattended operation; it draws less than 9 ma operating, less than 7 ma quiescent.

#### Durability

The sensor and electronics are integrated into a single unit and are enclosed and sealed in a durable shock resistant PVC housing.

#### Economical

The lightweight sensor and range tube assembly is easily mounted at any angle from which the tube is immersed to the lowest significant level with minimal site preparation. Sensor to Data Collection Platform separation up to 1,000 feet can be accommodated.



**A SMART INSTRUMENT**

The Aquatrak 5000 Sensor calculates the true average level even in the presence of waves and surging liquid surfaces. The Sensor can be configured via its communication ports for virtually any site-unique conditions. The sample rates, number of samples averaged, and data requested are selectable. Continuous measurements or exclusive data sets without outlier bias are standard operating modes.

**WAVES AND SEA STATE**

The US NOS standard averaging algorithm is used to determine the standard deviation for each data set. This value may be used in post processing to determine the average wave height during the sample period. .

**Technical Specifications**

Measurement	Accuracy
<p>Dynamic Range            Standard &gt;35 feet (10 meters)            Optional &gt;50 feet (15 meters)            Special 75 feet (23 meters)            Rate of Change <math>\pm 10</math> feet (<math>\pm 3</math> m/sec)            Units English or Metric            Resolution 0.0033 feet (1 mm)            Rate Proportionate 1.2 – 2.4 per sec            Sample Rate Averaged 1.0 per sec            over 2 to 255 Samples            Interval Host Determined</p> <p><b>Electrical</b>            Input Voltage 12.5 <math>\pm 2</math> volts DC            Operating Current 9 ma            Quiescent Current 7 ma</p> <p><b>Environmental</b>            Operating Temperature -40 to +55 °C            Storage Temperature -55 to +60 °C            Humidity 0 to 100%</p>	<p>Calibration            Standard <math>\pm 0.025\%</math>            Optional <math>\pm 0.01\%</math>            Nonlinearity <math>\pm 0.02\%</math>            Precision, Repeatability <math>\pm 0.01\%</math>            Stability, Drift, 1 year 0            Temperature Drift &lt;1 ppm/°C</p> <p><b>ASCII Serial Communication</b>            Selectable Baud Rate (RS-232) 300 to 9600            Format Serial ASCII            RS-232 N-8-1            SDI-12 (1200 Baud only) E-7-1</p> <p><b>Physical</b>            Sensor Assembly            Diameter 3.25 in (8.25 cm)            Height 9 in (22.8 cm)            Weight 2.5 lb (1.14 kg)            Shipping Weight (1 Carton) 5 lb (2.3 kg)</p>

**Aquatrak Corporation**  
 1100 East 25<sup>th</sup> Street  
 Sanford, FL 32771  
 TEL: 407-321-3655 FAX: 407-323-4944  
 E-mail: [gauges@aquatrak.com](mailto:gauges@aquatrak.com)